

Double Push Panic Buttons

PAB-S, PAB-W

Manufactured to BS EN50131 these panic buttons provide a modern and neat solution where a double push latching panic button is required. The PA microswitch is normally closed and will open only when both buttons are pressed.

Then tamper switch is normally closed, if the lid of the unit is removed the tamper switch will go open.

Available in white ABS or black ABS with a stainless steel cover.

Supplied with a reset key

| Specification | PAB-W | PAB-S |
|-----------------------|--|--------------------------|
| Tamper Switch Contact | SP 500mA@ 15vdc | SP 500mA@ 15vdc |
| PA Switch Contact | SP 500mA@ 15vdc | SP 500mA@ 15vdc |
| IPA | N/C going open | N/C going open |
| Tamper | N/C going open | N/C going open |
| Material | White ABS | Black ABS & Stainless |
| Security Grade | 3 | 3 |
| Environmental Class | 2 | 2 |
| Resistors | No | No |
| Dimensions | 84 x 65 x 26 mm | 84 x 65 x 26 mm |
| Weight | 0.15kg | 0.15kg |
| IP Rating | IP22 | IP22 |
| Approvals | UKCA and CE marked, ROHS compliant EN 50131-1:2006+A3:2020 PD6662:2017 | |



PAB-S



PAB-W

Dimensions - 84 x 65 x 26 mm

